



Canon PC-90 Specifications

	Floor-type universal reader-printer
Process:	Canon MP Cartridge plain-paper process; single component dry toner projection system
	Both negative and positive images of silver, vesicular or diazo film
Formats:	Roll Fiche Carrier 200 for fiche/16mm and 35mm roll films/M-Type 16 mm cartridge M-Type 16mm cartridges Fiche Carrier 190RII for fiche/jackets/aperture cards Autocarrier 100R for 16mm/35mm/ rollfilms Autocarrier 100C for ANSI/M-type 16mm cartridges Autocarrier 100M exclusive for M-type 16mm cartridges FS Controller 1 for ANSI/M-type cartridges; keyboard search and print control of blipped images
	Interchangeable grid-index plates for FC190RII 4-digit LED odometer for AC100R/AC100M/AC100C Trilevel blip control for FS Controller 1
	11-3/4" x 11-3/4" rear-projection type with print frame markings
	Zoom lenses 9.5x-16x, 10x-24x, 16x-32x, 30x-55x Single Magnification Lenses 12x, 24x, 48x, 85x
	Constant focus by floating lens system
Rotation:	Standard 360-degree optical image rotation
	8-1/2" x 11" (Letter size)
Capacity:	Front-loading 250-sheets cassette
Speed:	10 prints per minute; approximate warm-up time is 26 second
	1- 19 prints w/LED count-down indication
Control:	Manual adjustment dial Optional Automatic Exposure Control function
	MP Cartridge 20N for negative film, 20P for positive film
	24V 150W halogen lamp

s:	51-13/16" x 20-11/16" x 29-1/16"
	130.2 lbs
	Workstation 90 pedestals
Design and specifications are subject to change without notice	