



[Back](#)

Canon 550D Specifications

Type:	Desktop rotary microfilmer with built - in camera unit
Reduction Ratio:	42X, Canon lens MC20mm 1:4
Filming Mode:	Duplex
Film Supply:	16mm-100ft(30.5), or thin base 125/215 ft films on standard 93mm dia. reel
Film Takeup:	Standard 93mm dia. reel
Document Size:	5 1/8" - 9 1/16" (130-230mm) 2 3/8" - 4 11/16" (70-120mm) 0.002"-0.01" (0.05-0.3mm)
Conveyor Speed:	138ft/min (42m/min)
Feeder:	Autofeeder with gap adjustment and side guides
Stacker:	Adjustable guide for back/forward and left/right position
Endorser:	Optional B100 Endorser; Fixed stamping position by single impression type Die Drum 232 w/6 - digit dater Optional Inkroller; 32 (red), 33 (blue), and 35 (purple)
Exposure Control:	Automatic for stabilized illumination
Indexing:	(1) 6 - digit LED display Odometer counting every 5" of film run (2) 6 - digit date exposure with blip on film; 3 mode date setting is available
Switches and Controls:	On/Off switch, SPACE button Leader/Trailer making by SPACE button, MODE button for LED display selection, FEED ADJ. button for paper count - only DATE button for date recording
Indications:	6 - digit LED for Exposure counter. Odometer/Date, Film supply indicators, Film end LED, Lamp failure LED, Paper misfeed LED
Illumination:	2 x 60V 70W halogen lamps
Weight:	52 lbs. (24 kg)
Dimensions(HxWxD):	11" x 19 3/8 x 24 9/16 (280mm x 492mm x 624mm)

Design and specifications are subject to change without notice