



Canon MP-55 Specifications

Type:	Desktop-type reader-printer
Print Process:	Canon MP Cartridge plain-paper process; single component dry toner projection system
Film:	Negative images of silver, vesicular or diazo film
Film Carrier:	Built-in carrier for standard 4" x 6" (105mm x 148mm) fiche/jacket; Optional Roll Carrier 50 for 16mm rollfilm
Indexing:	interchangeable grid-index plates
Lenses:	Zoom/lenses: 18-36x, 21-42x, 16.5x/23.5x; 31.4x.41x with image Rotation <i>single Magnification: 17.2x, 19x, 23.5x, 29x,33x, 35.5x, 41x, 47</i> <i>prism lenses: 23.5x, 33x, 41x, 47x</i>
Focusing:	By lens focusing fins; constant focus with floating-lens system
Image Rotation:	360 degrees by prism lenses or 90 degrees by image rotation lenses
Print Size:	8-1/2" x 11" (Letter size)
Paper Supply:	Automatic stack-sheet feeding system (up to 50 sheets)
Print Speed:	4 prints per minute; warm-up time is 24 second
Multiprint:	1- 9 with countdown indication, or "F" mode (for continuous printing on stacked paper)
Density Control:	Manual Dial Adjustment
Light Source:	17V 60W halogen lamp
Supplies:	MP Cartridge 20N
Dimensions:	22-3/8" x 18" x 28-1/8"
Weight:	62 lbs
Accessory:	Dust Cover
Design and specifications are subject to change without notice	