



Minolta RP503 Specifications

Specifications:	
Type:	Desk-top microfiche and jacket reader-printer
Developing System:	Micro-Toning System (dry)
Microforms:	Microfiche, jackets, and (with optional adaptor) 16mm roll film
Screen:	12"x12" (305mm x 305mm)
Magnification:	17.0 x (for 24:1, 27:1 COM fiche) 20.0 x (for 20:1 source) 24.5 x (for 24:1 source) 29.0 x (for 42:1 COM fiche) 33.0 x (for 48:1 COM fiche) 38.0 x (for 42:1 source) 42.0 x (for 48:1 source)
Magnification change:	Sliding dual-lens turret
Image rotation:	360° by motorized auto-prism rotation
Printing System:	Positive prints from negative film Optional Positive prints from both negative and positive film
Exposure Control:	Automatic (manual override)
Indicators:	Self-diagnostics, LED indication
Copy Size:	Letter size (A4) - 8-1/2" x 11"
Printing Speed:	6 prints per minute
First Copy Speed:	14.5 Seconds
Warm-up time:	30 Seconds approx.
Multiple prints:	1-19 prints (led countdown indicator)
Paper supply:	Plain paper, Autofeed 150 sheet cassette
Light Source:	24V 250W halogen lamp
Dimensions:	20-7/8"(W) x 31-1/4"(D) x 24-7/32"(H)
Weight:	143lbs. (72.5kg)
Options:	Prism lens, Bi-Mode Kit, 16mm roll film adapter, cursor, partial print accessory.
Design and specifications are subject to change without notice	